

## IN THE CLAIMS

1. (Currently amended) Device (1) for the analysis or absorption measurement of a small quantity of a liquid medium (2) using light (3), which is guided through the medium (2) and then can be detected or analyzed photometrically, spectrophotometrically, fluorometrically, or spectrofluorometrically, wherein the device (1) ~~comprises~~ comprising a receiving point (4) area at a top thereof ~~in a position of use~~ for depositing or applying the medium (2) in drops, a light inlet (5) oriented horizontally ~~in a position of use~~ and located underneath the receiving point (4) in a housing (6), and a first device (7) located downstream of ~~behind~~ the light inlet (5) ~~providing and defining~~ a beam path for guiding the light received by the light inlet (5) upwards towards the receiving point (4), the device (1) has a reflector (8), which ~~is can be~~ attached detachably above the receiving point (4) opposite from the beam path extending from the light inlet; the reflector (8) has a defined spacing from the receiving point (4) ~~in a position of use~~, which is filled or can be filled by the medium (2) at least in an area aligned with the beam path of the first device (7) of the light passage; and a second device (9) is provided for guiding the light coming from the reflector (8) towards a detector.

2. (Currently amended) Device according to Claim 1, wherein the receiving point (4) ~~has can be~~ accessed as an externally accessible upper surface area ~~from above~~ and the medium (2) to be analyzed can be fixed or held by a force of gravity at the receiving point (4).

3. (Previously presented) Device according to Claim 1, wherein the receiving point (4) has dimensions such that the light (3) moving through the receiving point towards the reflector (8) and reflected back from the reflector is guided at least once through the receiving point (4) and/or through the medium (2).

4. (Previously presented) Device according to Claim 1, wherein a light guide or light-guiding fiber bundle (10) is arranged for guiding the light towards the receiving point (4) from the first device (7) and a light guide or a fiber bundle (11) for guiding the light coming from the reflector (8) and the sample is arranged between the receiving point (4) and the second device (9).

5. (Currently amended) Device according to Claim 4, wherein optics (12) comprising at least one convergent lens, which bundles the light and which is coupled optically with at least one of the light guide for guiding the light towards the receiving point (4) or the light guide for guiding the light coming from the reflector (8) ~~(s)~~ (10, 11), is provided underneath the receiving point (4) for the medium (2).

6. (Currently amended) Device according to Claim 5, wherein the receiving point (4) is an area recess on the top side of the device (1) underneath the reflector (8) and is formed by a boundary of the optics ~~or lens~~ (12) facing the receiving point ~~or by the light guides (10, 11) ending at the receiving point position~~, wherein the boundary of the lens or optics (12) and/or the ends of the light guides (10, 11) are set back is recessed relative to a top side (13) of a holder for the ~~lens or optics (12) or the light guides~~.

7. (Previously presented) Device according to Claim 6, wherein the ~~lens or~~ optics (12) coupled with the light guides (10, 11) are simultaneously formed as a closing window of the device (1), on which the sample of the medium (2) to be analyzed can be applied in drops.

8. (Previously presented) Device according to Claim 1, wherein the reflector (8) is a mirror or a reflecting prism and touches the sample of the medium (2) without

spacing in the position of use.

9. (Previously presented) Device according to Claim 1, wherein the measurement distance through the sample is twice as large as a spacing of the receiving surface (4) from a surface of the reflector (8) and the light travels twice through the spacing.

10. (Currently amended) Device according to Claim 1, wherein the reflector (8); ~~which can be set or attached detachably,~~ is ~~locked in rotation~~ rotatably fixed with and centered relative to the device (1) and the housing (6).

11. (Previously presented) Device according to Claim 9, wherein the spacing of the reflector (8) from the receiving point (4) is set by at least one spacer (16) between the reflector (8) and the housing (6) or a stop.

12. (Currently amended) Device according to Claim 1, wherein the device (1) has outer dimensions ~~[[of]]~~ corresponding to outer dimensions of a standard ~~[[a]]~~ cell, ~~which can be used~~ adapted for use in a photometer, spectrophotometer, fluorometer, or spectrofluorometer and ~~which is struck by~~ receives light therefrom, and the first and second devices (7, 9) ~~arranged in the interior of the device (1) for feeding or guiding light are arranged at a position~~ are positioned in the device (1), ~~at which inlet and outlet windows for the light (3) used for the measurement are provided in typical cells, wherein~~ such that the first device (7) for guiding light directs the light emitted by ~~[[a]]~~ the photometer, spectrophotometer, fluorometer, or spectrofluorometer towards the receiving surface (4) and the second device (9) for guiding light directs the light coming back from the measurement point towards the detector.

13. (Currently amended) Device according to Claim 1, wherein the device is

comprised of glass or plastic, ~~and has, in the area of the light inlet (5), as a the first~~  
guiding device (7)[[.]] comprises a tilted prism or a tilted mirror facing a shaft (18)  
or channel at a right angle to the light inlet for a light guide (10) and the second  
guiding device (9) comprises a second tilted prism or a tilted mirror facing a shaft or  
a channel at a right angle to the light outlet of parallel to the guide another light  
guide (11) ~~with a second tilted prism or tilted mirror, which is arranged at the~~  
~~opening and which lies opposite an outlet window for the light or forms the window.~~

14. (Currently amended) Device according to Claim 1, wherein the outer  
dimensions of a cross section of the device (1) ~~corresponds to those of~~ correspond to  
dimensions of a standard cell.

15. (Previously presented) Device according to Claim 1, wherein the outgoing light  
beam is aligned with the incoming light beam or encloses a right angle with the  
incoming beam.

16. (Previously presented) Device according to claim 14, wherein the outer  
dimensions equal 12.5 mm x 12.5 mm.

17. (New) Device according to Claim 4, wherein the receiving point (4) is an area  
recess on the top side of the device (1) underneath the reflector (8) and is formed by  
the light guides (10, 11) ending at the receiving point position, wherein the ends of  
the light guides (10, 11) are recessed relative to a top side (13) of a holder for the  
light guides.